

# SHEFFIELD METALS, TEST REPORT

# **SCOPE OF WORK**

ASTM E1646 WATER PENETRATION BY UNIFORM STATIC AIR PRESSURE DIFFERENCE ON 0.040" ALUMINUM 1-3/4" SNAPLOCK PANELS

# **REPORT NUMBER**

13448.04-450-44 RO

# **TEST DATE(S)**

05/07/18

ISSUE DATE REVISED DATE

08/14/18 N/A

# RECORD RETENTION END DATE

05/07/22

# **PAGES**

9

# **DOCUMENT CONTROL NUMBER**

ATI 00231 (09/05/17) RT-R-AMER-Test-2827 © 2017 INTERTEK





> Telephone: 561-881-0020 Facsimile: 717-764-4129 www.intertek.com/building

# **TEST REPORT FOR SHEFFIELD METALS**

Report No.: I3448.04-450-44 RO

Date: 08/14/18

## **REPORT ISSUED TO**

## **SHEFFIELD METALS**

5467 Evergreen Parkway Sheffield Village, OH 44054

#### **SECTION 1**

**SCOPE** 

#### **Product:**

Intertek Building & Construction (B&C) was contracted by Sheffield Metals, 5467 Evergreen Parkway, Sheffield Village, OH 44054, to perform testing in accordance with ASTM E1646, Standard Test Method for Water Penetration of Exterior Metal Boof Panel Systems by Uniform Static Air Pressure Difference, on their 0.040" Aluminum 1-3/4" SnapLock roof panels. Results obtained are tested values and were secured by using the designated test method(s). Testing was conducted at Intertek test facility in West Palm Beach, Florida. This report does not constitute certification of this product nor an opinion oxendorsement by this laboratory.

This report does not constitute certification of this product nor an opinion or endorsement by this laboratory.

# **SECTION 2**

# **SUMMARY OF TEST RESULTS**

Product Type: Metal Roof Panel

Series/Model: 0.040" Aluminum 1-3/4" SnapLock

Test Pressure(s): 6.24 psf

For INTERTEK B&C

COMPLETED BY:

TITLE:

SIGNATURE:

DATE: mmn:ab Melissa Nuttall

Technician Team Leader

- Product

08/14/18

**REVIEWED BY:** 

TITLE:

**SIGNATURE:** 

DATE:

Vinu Abraham, P.E.

Vice President – Global **Business Development** 

08/14/18

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample(s) tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Version: 09/05/17 Page 2 of 9 RT-R-AMER-Test-2827



> Telephone: 561-881-0020 Facsimile: 717-764-4129 www.intertek.com/building

# **TEST REPORT FOR SHEFFIELD METALS**

Report No.: I3448.04-450-44 RO

Date: 08/14/18

# **SECTION 3**

# **TEST METHOD**

The specimen was evaluated in accordance with the following:

**ASTM E1646-95 (2011),** Standard Test Method for Water Penetration of Exterior Metal Roof Panel Systems by Uniform Static Air Pressure Difference

ASTM E8/E8m-16a, Standard Test Method for Tension Testing of Metallic Materials.

# **SECTION 4**

# **MATERIAL SOURCE**

The test specimen was provided by the client. Representative samples of the test specimen will be retained by Intertek B&C for a minimum of four years from the test completion date. Installation of the tested product was performed by the client.

# **SECTION 5**

# **EQUIPMENT**

Lab Pack: Portable blower with pressure measuring device

#### **SECTION 6**

# LIST OF OFFICIAL OBSERVERS

NAME	COMPANY
Ronald Green	Intertek B&C
Jacob Patterson	Intertek B&C
Veron Wickham	Intertek B&C
Melissa Nuttall	Intertek B&C
Alan Rule	Intertek B&C
Vinu Abraham P.E.	Intertek B&C



> Telephone: 561-881-0020 Facsimile: 717-764-4129 www.intertek.com/building

# **TEST REPORT FOR SHEFFIELD METALS**

Report No.: I3448.04-450-44 RO

Date: 08/14/18

#### **SECTION 7**

# **TEST SPECIMEN DESCRIPTION**

**Product Type**: Metal Roof Panel

Series/Model: 0.040" Aluminum 1-3/4" SnapLock

Test Pressure(s): 6.24 psf

# **Product Size(s):**

# **All Test Specimens**

OVERALL AREA:	WIDTH		LENGTH	
9.3 m <sup>2</sup> (100.0 ft <sup>2</sup> )	millimeters	inches	millimeters	inches
Overall Size	1676	66	1321	52
Panel Coverage	406	16	1321	52

#### **Test Deck Construction:**

The unit was installed over a Pine wood deck measuring 68" wide x 54" long. The deck utilized a 2x4 Pine wood frame with studs spaced 16" on center, running parallel to the seams of the roof panels. #8 X 3" long Torx flat head screws were used to secure all frame members.

# **Roof System:**

Moor bysterm		
COMPONENTS	DETAILS COMPANY	ATTACHMENT METHOD
Clip	The 1.86" high x 2.032" wide x 3.50" long clips were constructed from 18 Ga steel.	The clips were spaced at 18" on center and attached to the studs using two #10-13 x 1" pancake head fasteners per clip.
1-3/4 SnapLock Panels	The panels were constructed from 0.040" aluminum and had a 16" coverage width. Three full and two partial width panels were tested.	The male leg of the panels were secured using clips spaced 18" on center. The female leg of the panels snap-fit to the male leg of the adjacent panels. A 1/8" continuous bead of Novaflex metal roof sealant was used at the seams on the underside of the peak of female leg of the panel. #12 x 1-1/4" HWH with weather seal washer self-drilling screws were used at the perimeter of the panels spaced 3" on center. The perimeter was sealed with butyl tape and silicone.



> Telephone: 561-881-0020 Facsimile: 717-764-4129 www.intertek.com/building

# **TEST REPORT FOR SHEFFIELD METALS**

Report No.: I3448.04-450-44 RO

Date: 08/14/18

#### **SECTION 8**

# **TEST RESULTS**

TITLE OF TEST	RESULTS	ALLOWED	NOTE 🕠
Preload	No Damage	No	1-4/1/10
+15 psf / -15 psf	No Damage	Damage	160
Water Penetration,		No	CAN!
per ASTM E 1646	No leakage	No Leakage 🔇	2, 3, 4
at 6.24 psf		Leakage	`

Note 1: Pre-loads were held for 10 seconds with a 2 minute recovery period after removal of each pre-load. The pre-load cycle was performed 3 times.

*Note 2: Testing was performed at a 0° slope.* 

Note 3: Water penetration testing was performed for 15 minute duration.

Note 4: Panel surface temperature prior to testing was 97°F. Panel surface temperature during testing was 82°F. The ponded water depth during testing was 1/2 inches.

Version: 09/05/17 Page 5 of 9 RT-R-AMER-Test-2827



> Telephone: 561-881-0020 Facsimile: 717-764-4129 www.intertek.com/building

# **TEST REPORT FOR SHEFFIELD METALS**

Report No.: I3448.04-450-44 RO

Date: 08/14/18

#### **SECTION 9**

#### **TENSILE TEST RESULTS**

Tensile tests were conducted on two specimens from each panel sample. The specimens were machined from the metal members to the dimensions of the sheet-type 0.5" wide specimen given in Figure 1 of ASTM E8. The coating on the specimens was removed from the reduced section prior to testing. Tensile properties were determined utilizing a Satec Universal Test Machine (ICN: Y002011) equipped with a 5,000 pound load cell (ICN: 65607) and a Class C extensometer (ICN: Y002015)The test was run at a crosshead speed of 0.2 in/min.

Specimen No.	Base Thickness (in)	Yield Strength (ksi)	Tensile Strength (ksi)	Modulus of Elasticity (ksi)	Reduction of Area (%)	Elongation (%)
1	0.0298	21.7	26.1	11,211	11	10.3

#### **SECTION 10**

# **CONCLUSION**

The product met the specified performance requirements.

The product met the specified performance requirements.

The product met the specified performance requirements.

Version: 09/05/17 Page 6 of 9 RT-R-AMER-Test-2827



> Telephone: 561-881-0020 Facsimile: 717-764-4129 www.intertek.com/building


# **TEST REPORT FOR SHEFFIELD METALS**

Report No.: I3448.04-450-44 RO

Date: 08/14/18

# **SECTION 11**

### **DRAWING**





Version: 09/05/17 Page 7 of 9 RT-R-AMER-Test-2827




> Telephone: 561-881-0020 Facsimile: 717-764-4129 www.intertek.com/building

# **TEST REPORT FOR SHEFFIELD METALS**

Report No.: I3448.04-450-44 RO

Date: 08/14/18



Intertek | Report #: | 13448.04.450.44 | Oste: | 08/14/18 | Verified by: | Law Coul.

Version: 09/05/17 Page 8 of 9 RT-R-AMER-Test-2827



> Telephone: 561-881-0020 Facsimile: 717-764-4129 www.intertek.com/building

# **TEST REPORT FOR SHEFFIELD METALS**

Report No.: 13448.04-450-44 RO

Date: 08/14/18

# **SECTION 12**

# **REVISION LOG**

0	08/14/18	N/A N/A	Original Report Issue	ENT FROM THE SAN TECHNOLOGY
		ot Reduction	AND THE STATE OF T	J.H. FRONTHE SMITE
		ot ROUCE!	A RIVINA WITHOUT WAS TEN CONG	SHI FROM THE SM.
C REPORT S NOT TO BE CH	HANGEDALTERED	Othr		
ROFISHOTION				

Version: 09/05/17 Page 9 of 9 RT-R-AMER-Test-2827