METAL ROOFING SYSTEMS

SMI 1.5" SnapLock 450+ Standing Seam

Panel Information:

Panel Type: Standing Seam
Panel Seam: SnapLock
Panel Width: 16"
Seam Height: 1.5"

Panel Material: 22 GA - 24 GA Min

Panel Surface: Smooth / Embossed Optional Panel Clip: Required Per Engineering

Minimum Slope: 3/12 Substrate: Plywood

Panel Testing:

Uplift Resistance: UL 90

Hail Rating: Class 4 Impact UL 2218


Fire Rating: UL Class A TDI Approval: RC-564

Panel Notes:

- With this 24 GA, 16" wide panel engineering, you may opt to use heavier gauge coil and narrower width panels. Clip spacing will not change.
- This panel uses a 20" coil.
- This panel uses 4-1/8" of material to form the panel.
- If you take the square footage of the roof and multiply that by 1.25, the total will be the amount of coil needed to manufacture the panels.
- This panel is approved for Weathertight Warranties.









CLEVELAND: 800.283.5262
ATLANTA: 800.929.9359
DALLAS: 877.853.4904
DENVER: 877.375.1477
SAN JOSE: 408.916.3262
LA MIRADA: 562.383.9800
sheffieldmetals.com