



TRIANGLE FASTENER CORPORATION

SIZES

Description	Attachment Thickness	Part Number	Carton Quantity	Wt Per M Pcs
#14-13 x 9" DP1*	5.875" - 8.500"	149000C1	500 pcs	61.0#

FASTENER PROPERTIES

Thread Type and Point	Thread Major Dia.	Material	Head Dia.	Head Thickness	Drive	REV JC070312 Finish
#14-13 DP1	.238"	C1022	.500"	.090"	#2 Sq	.0003" Zinc & Yellow TRI-SEAL™ Coated

PERFORMANCE SPECIFICATIONS

Fastener Diameter & Material	<i>Minimum Ultimate</i>			
	Thread Diameter	Tensile (lbs.)	Shear (lbs.)	Torsional (lbs-in)
#14-13 / Carbon	0.235"	3,620	2,500	115

PULLOUT LOADS

Fastener Diameter & Point	<i>Material Thickness</i>										
	24 ga (.024")	22 ga (.021")	20 ga (.030")	18 ga (.048")	16 ga (.060")	14 ga (.075")	12 ga (.105")	1/8" (.125")	3/16" (.188")	1/4" (.250")	1/2" (.500")
#14-13 DP1	338	574	720	961	1,000	1,350					