

Kalida-Kote™
In-House
Painting
Available For
Custom Color
Matching, Fast!



Buttonhead	D Rivet Dia.	Drill No. & Hole Size	H Head Dia. Nom.	E Head Height Max.	L Rivet Length Max.	Grip Range	Typical Ultimate Strength (Lbs.) (newtons)	
Material	Inch (mm)	(mm)	Inch (mm)	Inch (mm)	Inch (mm)	Inch (mm)	Shear	Tensile
<i>Stainless Rivet</i>					.212 (5.4)	.032-.062 (0.8-1.6)		
<i>Stainless Steel</i>					.275 (7.0)	.063-.125 (1.7-3.2)		
<i>Mandrel</i>					.337 (8.6)	.126-.187 (3.3-4.8)		
IFI Grade 50	1/8" (.125)	#30 (.129-.133)	.250	.040	.400 (10.2)	.188-.250 (4.9-6.4)	520	600
Open End	3.2	3.3 (3.28-3.38)	6.35	1.02	.462 (11.7)	.251-.312 (6.5-7.9)	2310	2660
					.525 (13.4)	.313-.375 (8.0-9.5)		
					.650 (16.5)	.376-.500 (9.6-12.7)		

Technical Information

Diameter	Body	Mandrel	Shear	Tensile
1/8"	Steel	Steel	280	410
1/8"	Aluminum	Steel	180	270
1/8"	Aluminum	Aluminum	150	180
1/8"	Stainless	Stainless	520	600
1/8"	Copper	Brass	215	300
1/8"	Aluminum	Steel	240	280
3/16"	Steel	Steel	600	870
3/16"	Aluminum	Steel	440	700
3/16"	Aluminum	Aluminum	280	430
3/16"	Stainless	Steel	1150	1300

Drill Bits



Use the correct drill bit to assure proper rivet performance.

Rivet Diameter **Drill Bit Size**
1/8" #30

In-Stock Colors #42 - #43 - #44 Call for Sizes

Aged Copper	Matte Black
Almond	Medium Bronze
Ash Gray	Musket Gray
Aztec Gold	Pacific Blue
Banner Red	Polar White
Bone White	Red Clay
Burnish Slate	Roman Bronze
Cape Clue	Royal Blue
Charcoal Gray	Rustic Red
Cherokee Blue	Sage
Classic Green	Sahara Tan
Cocoa Brown	Sierra Tan
Colonial Red	Seaport
Colony Green	Slate Blue
Copper Penny	Slate Gray
Corcován	Snow White
Country Red	Snowdrift
Dark Bronze	White
Desert Sand	Stone White
Emerald Green	Teal Green
Fern Green	Terra Cotta
Hartford Green	Winter Blue
Hawaiian Blue	
Light Stone	
Mansard	
Brown	